



Low Profile 6" LED Surface Mount Disc



Model No. CH-MASD0524-30

The 6-inch surface mount LED downlight is a low profile installation solution designed to fit the tightest of spaces. The driverless DOB driver onboard technology allows this fixture to fasten to most 3 or 4 inch round, octagon or square junction box or shallow pan box eliminating the need for recessed housing. ETL certification and suitable for exterior wet locations. This fixture is classified as a directional light source.

☒ Finish: White ☒ Dimensions: Diameter 7.43" x Height 1.09" ☒ Weight: 0.45 lbs.

- Easy to install: fits all standard 3" or 4" J-box
- Die Cast Aluminum
- 50,000 rated hours
- Ceiling or wall mount
- Accessories available for 4", 5", 6" recessed housing

Specifications

Nominal Wattage:	15W	Input Voltage:	120V
Dimming:	Dimmable (Triac/ELV 10 – 100%)	Environment	Indoor Outdoor (wet location)
Certificates:	cETLus	Color Temp:	3000K (also available in 2700K, 4000K, 5000K)
Lumens:	1200	CRI:	> 90
Certificates:	cETLus	Operating Temp:	-4 to 104 F

Compatible with the following dimmers: Cooper (SALO6P); Leviton (69631-LI, 6674, 6672, 6633-P); Lutron (S600P, TGCL-153P, PD-6WCL, DVCL-153P-WH, MACL-153M-WH, GT-600P, GTCL-153P-WH, CT-600PR-IV)

www.kamalighting.com

 kama@kamalighting.com

At KAMA Lighting, our mission is to manufacture the highest quality lighting fixtures that exceed the demands of our customers' design intent and budget. Our team truly understands the importance of budget in the construction industry and our lighting solutions are tailored to meet financial goals without compromising quality.

Whether you are a builder, a lighting distributor or an electrician, KAMA Lighting has lighting solutions for all your needs. If you don't find a KAMA product that fits your required "look" or design intent, rely on our "Made To Spec" program to design any fixture you desire down to the last detail. Contact your local KAMA Lighting representative today to ask about our "Made To Spec" program.